





Redundant SIM Slots for Multiple Carriers

Redundant SIM slots with automatic switching for reliable network. You can set the WiFi In Motion™ MAX to automatically switch SIM cards when you're in danger of exceeding a data cap. It also allows you to travel across borders without changing SIM cards manually.



CIPA Compliant Filtering

The WiFi In Motion™ MAX also delivers CIPA compliant content filtering, offering peace of mind to parents and administrators alike. With WiFi In Motion, children can now safely browse the web.





Captive Portal with Social Wi-Fi

The WiFi In Motion™ MAX comes with a customizable captive portal that allows passengers to login with Facebook, LinkedIn and Twitter. As they log in, you can see insightful reports on demographics.



Certified Toughness

In addition to rugged metal enclosure, WiFi In Motion™ MAX has certifications on: Shock and vibration resistance (EN 61373:1999, IEC 61373:1999) Railway applications (EN 50155) Electromagnetic Compatibility (EN 61000)



CCTV Live Look-in

With WiFi In Motion™, now district staff and emergency services personnel can have real-time remote camera access, making the safety of the driver and children a reality.



GPS Fleet Management

Track your devices wherever they are using our interactive maps. Check vehicle speed, cellular coverage, and traffic conditions. Play back route histories in real-time.





Technical Specifications

MAX

WAN Interface 1x FE

Embedded LTE/3G Modem with Redundant SIM Slot

LAN Interface 2x FE

Wi-Fi Interface 802.11b/g/n 300 Mbps Wi-Fi WAN and/or AP

Router Throughput 100Mbps

Recommended Users 1-60

Cellular and GPS Antenna Connector 2x SMA Antenna Connectors

1x SMA GPS Antenna Connector

1x Wi-Fi Connector

Power Input DC Jack/Terminal Block: 12V – 48V DC

Power Consumption 16W (max.)

Dimensions 5.8 x 5.0 x 1.6 inches

147 x 128 x 40 mm

Weight 0.96 pound 435 grams

Operating Temperature -40° – 149°F

-40° – 65°C

Humidity 15% – 95% (non-condensing)

Certifications FCC, CE, RoHS, E-Mark

RF Port Lightning Immunity: ITU-T K.20 (+/- 1.5 kV)

EN 61373:1999 IEC 61373:1999 : Shock and Vibration Resistance

EN 50155: Railway Applications EN 61000: Electromagnetic Compatibility

Warranty 1-Year Limited Warranty



5.8 inches / 147mm





Features

WAN

Support for PPPoE, Static IP, DHCP WAN Link Health Check Bandwidth Allowance Monitor Support for Dynamic DNS services WAN Port Convertible into LAN Port

LAN

DHCP Server for LAN Clients Extended DHCP Options DHCP Reservation DNS Proxy for LAN Clients VLAN on LAN Support Per-Port VLAN Support Security
Stateful Firewall
DoS Prevention
Web Blocking
Wef Filtering Blacklist

Load Balancing
Intelligent Failover
Session Persistence
Per-Service Load Distribution
Multiple Algorithms

Advanced QoS Individual Bandwidth Limit Application Prioritization SIP, HTTPS, VPN QoS Custom Application QoS Complete VPN Solution

PepvPN/SpeedFusion Hot Failover Site-to-Site VPN Hot Failover 256-bit AES Encryption

Pre-shared Key Authentication Dynamic Routing X.509 Certificate Support IPsec VPN (Network-to-Network)

X.509 Certificate Support*

Networking NAT and IP Forwarding Static Routes Port Forwarding Many to One, One to One NAT NAT Pool SIP ALG, H.323 ALG UPnP, NAT-PMP **Captive Portal Support**

Support for Wired and Wireless LAN Clients Support for RADIUS Authentication Time and Usage Quotas on Open Access

Built-in Customizable Splash Page

Global Positioning System
Integrated GPS
Device Location Map
Location Tracking Data with InControl 2
Fleet Management with InControl 2

Available as optional feature.

"With SinglePoint's CIPA compliant content filtering software, now students can work on school related material via SinglePoint's robust Wi-Fi, offering parents and educators alike peace of mind. Their products also allow school district remote access to on board CCTV and other mission critical systems, allowing for enhanced safety of district students and staff."

Stephen Shoemaker, FirstStudent





SinglePoint Communications, Inc.

7990 SW Cirrus Dr Beaverton, OR 97008 866.959.9434 | www.yoursinglepoint.com

©2015 SinglePoint Communications. All Rights Reserved. Trademarks are the property of their respective owners. Specifications subject to change without notice. E&OE.